

IN THE SPECIFICATION:

Please amend the first full paragraph on page 10, beginning on line 9 as follows:

Next provided is a coil spring 32. The coil spring has an upper end 34 and a lower end 36. The upper and lower ends are positioned on the base plate and sized to be slightly longer than height of the interior recess of the case. ~~The central portion has a downwardly extending finger 38 for positioning the spring.~~

Please amend the paragraph beginning on Page 10, Line 14 spanning Page 15 as follows:

Provided last is a follower 42. The follower is positioned within the recess upon the spring. The follower is fabricated of a heat treated stainless steel and is sufficiently thin to provide a spring-like resilience. The follower has a central section 44. The central section has a downwardly extending front leg 46. This front leg is curved to conform to the shape of the rounded front face of the case terminating in an arcuate lowermost extent. The central section also has a downwardly extending flat rear leg 48 which conforms to the shape of the flat rear face of the case. The front leg and the central portion are less wide than the rear leg and the central section.

The front and rear legs are adapted to smoothly slide downwardly without binding within the case with the addition of bullets to the recess and the compression of the spring. The front and rear legs are further adapted to smoothly slide upwardly without binding within the case with the removal of bullets from the case and the force of the spring. The central portion of the follower has a downwardly extending finger 38 for positioning the spring.